

## SPECIFICATION SHEET

Commodity : Polyester Chips Textile Grade Flame Retardant

Application : Yarns, Fibers, Nonwovens

Origin : Taiwan

分析項目 Test Item	單位 Unit	測試方法 Test Method	標準值 Standards
極限黏度 Intrinsic Viscosity	dl/g	ASTM D-2857	0.690 ± 0.020
色值L(白度) Color L Value		CNS 13584 L3235	62.5 ± 4
色值b(黃度) Color b Value		CNS 13584 L3235	4.2 ± 3.0
熔點 Melting Point	°C	CNS 13584 L3235	238.5 ± 3.0
二乙二醇 DEG	%	1143201-D3-311	3.30 ± 0.70
二氧化鈦含量 Tio2 Content	%	1143201-D3-316	0.60 ± 0.10

Packing : 1000KGS IN PP WOVEN JUMBO BAGS

Container Loading : 20MT (20BAGS) IN 1 X 20FT CONTAINER



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.  
Sayaca Cad. Ekol Center  
Kat 2 No:50 Beylikduzu  
Istanbul - Turkey  
Tel: +90 212 856 05 01  
www.tesport.com  
resin@tesport.com