

01 January 2019

SALES SPECIFICATIONS

ETHYLENE GLYCOL INDUSTRIAL GRADE SPECIFIED MATERIAL: 000101234172

| TEST ITEM | METHOD | ETHYLENE GLYCOL INDUSTRIAL GRADE |
|---------------------------------------|---------------|----------------------------------|
| Purity, %wt, minimum | BY DIFFERENCE | 99.1 |
| Diethylene Glycol, %wt, maximum | ASTM E2409 | 0.6 |
| Acidity, ppm, maximum, as Acetic Acid | ASTM E2679 | 20 |
| Iron, ppm, maximum | ASTM E1615 | 1 |
| Water, %wt, maximum | ASTM E1064 | 0.3 |
| Color, Platinum-Cobalt Units, maximum | ASTM D5386 | 10 |
| Appearance | ASTM E2680 | Pass |

Typical values for Specific Gravity (20/20°C): 1.1151 – 1.1156



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.
Sayaca Cad. Ekol Center
Kat 2 No:50 Beylikduzu
Istanbul - Turkey
Tel: +90 212 856 05 01
www.tesport.com
resin@tesport.com